



# Aluminium Alloy Plates, Sections, Bars, Castings & Forgings

<b>Manufacturer</b>	<b>COSMOS ALUMINIUM A.E</b>
<b>Address</b>	8TH KM NATIONAL ROAD LARISSA-ATHENS, P.O. BOX 1379, Larissa, 411 10, Greece
<b>Type</b>	Aluminium Alloy

This approval is subject to compliance with the Rules for the Manufacture, Testing and Certification of Materials. The full details of the processes and grades to which this approval applies are given on subsequent pages of this certificate.

This certificate is issued to the named manufacturer, and is valid until the expiry date specified. Lloyd's Register is to be notified of any change that may affect the validity of this certificate, and reserves the right to cancel or withdraw this certificate.



71 Fenchurch Street, London, EC3M 4BS, United Kingdom

**Clive Arnold**

Metallurgy Team - Lead Specialist to Lloyd's Register EMEA  
A member of the Lloyd's Register group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.



## Aluminium Alloy Plates, Sections, Bars, Castings & Forgings

Aluminium Alloy	Refining & Semi Finished	Grades	Maximum Diameter	Units
Homogenised	-	6082	203.00	mm
Aluminium Alloy	Bars	Grades	Maximum Thickness	Units
-	-	6082-T6	80.00	mm
Aluminium Alloy	Sections	Grades	Maximum Thickness	Units
-	-	6082-T6	20.00	mm

### Additional Remarks

Aluminium alloy logs/billets manufactured by Airslip Casting Technology process.

Bars of square, rectangular, round and hexagonal up to 80 mm thickness.

Bars within circumscribed circle diameter maximum 250 mm x 70 mm thickness.

Section profiles of various shapes (flat and hollow) up to 20 mm thickness.

Sections from within circumscribed circle diameter maximum, 250 mm x 20 mm thickness.



71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

